

U SERIES CONNECTION KITS FOR SELF REGULATING HEATING CABLE CABLE

- For SRL & SRME Heating Cable
- NEMA 4X, Liquid Tight Enclosure
- Exposure Temps. to 482 °F (250 °C)
- Corrosion Resistant
- Non-Flammable
- High Strength and Rigidity
- Stainless Steel Hardware
- Captive Connection Blocks
- Captive Cover screws

Approvals

UL Listed

Ordinary Areas

CSA Certified

Ordinary Areas

Class I, Div. 2, Groups A, B, C, and D

Class II, Div. 2, Groups F, G

FM Approved

Ordinary Areas

Class I, Div. 2, Groups B, C, D

Class II, Div. 2, Groups E, F, G

Class III

UPC,

Power Connection Kit

NEMA-4X rated junction box designed for connecting power wiring to one SRL or SRME heating cable. This kit provides water-resistant cable entry for one cable, enclosure support, terminal block, and a water-resistant corrosion-resistant enclosure with a 3/4" opening for power wiring. A pipe strap (PS series) is required for attaching this model to a pipe. A small pipe adaptor (SPA) is required for pipe sizes less than 1-1/2".



UMC,

Multiple Entry Connection/Tee/Slice Kit

NEMA-4X rated junction box for connecting up to three SRL or SRME heating cables. This kit can be used for teeing or splicing cables and has a removable 3/4" entry plug that allows the kit to provide power connection for up to three cables. This kit provides water-resistant cable entries, enclosure support, terminal block, and a water-resistant corrosion-resistant enclosure. A pipe strap (PS series) is required for attaching this model to a pipe. A small pipe adaptor (SPA) is required for pipe sizes less than 1-1/2".



UES,

Above Insulation End Seal Kit

NEMA-4X rated end seal for terminating SRL or SRME heating cable. This kit provides water-resistant pipe standoff to bring the cable end outside the insulation for easy access. A pipe strap (PS series) is required for attaching this model to a pipe. A small pipe adaptor (SPA) is required for pipe sizes less than 1-1/2".



UPC, Single Entry Power Connection Kit

Kit Includes:

- 1 Junction box with DIN rail & terminal block
- 1 Compression fitting
- 1 Locknut
- 1 Silicone termination boot
- 1 Pipe standoff
- 1 O-ring
- 1 Self-regulating cable grommet
- 1 Constant wattage cable grommet



UMC, Multiple Entry Connection Kit

Kit Includes:

- 1 Junction box with DIN rail & terminal block
- 1 Compression fitting
- 1 Locknut
- 3 Silicone termination boots
- 1 Pipe standoff
- 1 O-ring
- 1 Self-regulating cable grommet
- 1 Constant wattage cable grommet



UES, Above Insulation End Seal Kit

Kit Includes:

- 1 End cap
- 1 Pipe standoff
- 1 Self-regulating cable grommet
- 1 Constant wattage cable grommet
- 2 Compression rings



RTES, Under Insulation End Seal Kit

Kit Includes:

- 1 End cap
- 1 Pressure plate
- 1 Self-regulating cable grommet
- 2 Compression screws



SPA, Small Pipe Adapter

Used with UPC, UMC, UES and SSK kits on pipe sizes less than 1.5"

