

USL END OF CIRCUIT CONNECTION KIT

- For SRL & SRME Heating Cable
- NEMA 4X, Liquid Tight Enclosure
- Exposure Temps. to 482 °F (250 °C)
- Corrosion Resistant
- Non-Flammable
- High Strength and Rigidity
- Stainless Steel Hardware

USL, Signal Light Kit

NEMA 4X rated end seal designed to power or seal one cable and indicate power on with 120 V, 208-240 V or 277 V LED indicator. Designed for use with SRL and SRME cables. Provides water-resistant cable entry for one cable. Includes enclosure support, terminal block, and corrosion-resistant wiring enclosure.

This kit is composed of the UPC power connection kit and a Class I Div 2 listed pilot light.

UPC's FM Listing: 126961
Pilot Light's UL Listing: NOIV.E157436
Pilot Light's T-Rating: T4A

USL Part Numbers:

USL-1: 120 V
USL-2: 208-240 V
USL-3: 277 V



USL, Signal Light Kit

Kit Includes:

- 1 Junction box with DIN rail & terminal block
- 1 Compression fitting
- 1 Locknut
- 1 Silicone termination boot
- 1 Pipe standoff
- 1 O-ring
- 1 Self-regulating cable grommet
- 1 Constant wattage cable grommet
- 1 LED light assembly



SPA, Small Pipe Adapter

Used with USL for pipe sizes less than 1.5"

